## Minitek® 1.00mm

**Product Presentation** 

**Amphenol Information Communications and Commercial Products** 

**≣FCi Basics** 

## **Amphenol ICC**

### Agenda



- Value Proposition
- Product Specifications
- Features & Benefits
- Part Numbers
- Markets & Application
- Marcom Collaterals

### **Value Proposition**



Minitek® 1.00mm is low profile with a current rating of 1.0A per contact. These connector are designed for small pitch wire to board application with gauge range from 28 to 32 AWG. Available in single row and 2 to 20 circuits.

Crimp, snap-in header and receptacle contacts are used to terminate 28AWG-32AWG wires. Header and receptacle housings allow Wire-To-Board configurations. Available in vertical and R/A component. These IR reflow soldering headers are available in surface mount configurations

### **Product Specifications**



#### **Product Facts**

- Wire-to-board connectors with 1.0mm centerline.
- Single row, 2-20 positions
- Solution Vertical / Right Angle SMT pin header
- Available in UL94V-0 flammability rated PA9T
- Products are lead free to help promote a cleaner environment
- UL approved

#### **Performances**

Current Rating : Up to 1A
Insulation Resistance : 100M ΩMin
Voltage rating : 500V rms

#### **Environmental**

■ Operating temperature range: -25°C to +85°C

#### **Mechanical Performances**

Mating Force : Refer to product spec.Unmating Force: .Refer to product spec.

■ Durability : 30 cycle

#### **Mechanical Performances**

Product Spec : GS-12-1465Package Spec : GS-14-2615

### **Features & Benefits**



| Features                                 | Benefits                            |  |
|--|-------------------------------------|--|
| Small pitch wire to board                | Capable for 1.0A                    |  |
| Low profile design                       | Save PCB space                      |  |
| UL94V-0 flammability rated PA9T material | High Flammability rating            |  |
| RoHS compliant and lead-free             | Meets health and safety requirement |  |
| Halogen-free resin material              | Meets environmental requirement     |  |

### **Part Numbers**



| AFCi P/N | Configuration  | Row    | Positions | Plating           | Product View   |
|----------|----------------|--------|-----------|-------------------|--|
| 10147605 | Vertical SMT   | Single | 2-20      | Tin<br>Gold Flash | The state of the s |
| 10147606 | R/A SMT        | Single | 2-20      | Tin<br>Gold Flash | and the same of th |
| 10147603 | Receptacle HSG | Single | 2-20      | N/A               |  |
| 10147604 | Femal Terminal | N/A    | N/A       | Tin<br>Gold Flash | mmmm   |

### **Application**





Servo motor



Patient Monitor



- DVDs
- Air Conditioning
- PCs
- Mobile POS terminals
- Set-Top Boxes
- Notebook PC
- LCDs
- Smart meters
- LCD TVs
- PDPs
- Digital TVs
- Small OA Machines

# **Amphenolicc**

### THANK YOU