


1.00mm Pitch FFC/FPC – F54L Series

VERTICAL A TYPE ZIF FLEX CONNECTOR

F54L series are 1.00mm pitch vertical ZIF flex connectors with slider mechanism and surface mount termination. These connectors feature a height of 4.25mm come in 4 to 30 contacts. These series feature a cable thickness of 0.30mm and provide enhanced durability of 30 mating cycles. The connectors come with a robust design and prevent solder and flux wicking. These are ideal for automotive, data, industrial, communication, consumer, and medical applications.

- Easy to operate and strong FFC/FPC retention makes it vibration-proof
- Ensures high solderability and high durability



TARGET MARKETS



FEATURES

- ZIF (Zero Insertion Force) mechanism
- Slider mechanism
- Design against solder and flux wicking
- High-temperature thermoplastic housing
- 4 to 30 positions available
- Lead and halogen-free

BENEFITS

- Absence of frictional mating wear resulting in high mating cycle life
- Easy to operate and strong FFC/FPC retention makes it vibration-proof
- Ensures high solderability
- Wide operating temperature range of -40°C to $+105^{\circ}\text{C}$
- Comprehensive range to satisfy different customer requirements
- Meets environmental, health, and safety requirements

▶ 1.00mm Pitch FFC/FPC – F54L Series

TECHNICAL INFORMATION

MATERIAL

- Housing: LCP, Natural color (UL94V-0)
- Slider: PA9T, Black color (UL94V-0)
- Contact: Phosphor Bronze, T=0.20mm
- Anchor-plate: Brass, T=0.40mm
- Mylar: T=0.10mm, Thermostable, Yellow color

MECHANICAL PERFORMANCE

- FFC/FPC Retention Force: 0.1~2.25kgf/min. (initial), after 30 cycles: 0.06~2.08kgf/min.
- Terminal Retention Force: 100gf/terminal min.
- Anchor-plate Retention Force: 400gf/plate min.
- Durability: 30 mating cycles

ELECTRICAL PERFORMANCE

- Voltage Rating: 50VAC/VDC
- Current Rating: 0.5A
- Contact Resistance: 30MΩ max.
- Insulation Resistance: 500MΩ min.
- Dielectric Withstanding Voltage: No short or breakdown after 500VAC, 2mA, 1min.

PACKAGING

- Tape & Reel

APPROVALS AND CERTIFICATIONS

- UL File Number: E106764
- RoHS compliant

SPECIFICATION

- Aorora Product Specification: IS.EQC.291

ENVIRONMENTAL

- Operating Temperature Range: -40°C to +105°C

TARGET MARKETS/APPLICATIONS



Car Multimedia
Car Navigation
Dashboard
PND



Base Station
Power
Switches



Notebook
Tablets
Wearables
Gaming
DSC
LCD & PDP TV



Router
Server
ODD
HDD




Sensing Element
Monitoring Camera
Human Machine Interface
Industrial PC
Robotics



Ultrasonic
Patient Monitor
MRI
CT
Infusion Pump

PART NUMBER SELECTOR



AORORAF54L1024EA4