

Modular Jack – RJE05 Series

CAT5, RIGHT ANGLED, LOW PROFILE THT, SINGLE PORT CONNECTOR

The RJE05 single port series of Modular Jacks meets CAT5E performance per EIA-568-C.2 standards. It supports 100 BaseT Ethernet data rate and transmission frequencies up to 100MHz. The available shielding enhances EMI performance and network speed verification. These connectors are highly durable with 750 mating and unmating cycles and supports an operating temperature of -55°C to + 85°C, making them suitable for a wide range of environmental conditions.

- Supports CAT3/5 Ethernet Protocols
- Tab Down Through Hole
- RoHS compliant



TARGET MARKETS



FEATURES

- Available in 6P6C and 8P8C
- Standard size
- Accommodates industry standard plugs
- Wave / Reflow compatible
- Board Lock Option
- Meets CAT5 as per EIA-568-C.2

BENEFITS

- Customers can opt for RJ11 and RJ45 applications
- Optimizes the PCB
- Can mate successfully with all types of standard plugs
- Economical process for soldering to PCB, saving time and money
- Accommodates a wide range of EMI needs
- Supports up to 100 BaseT Ethernet

TECHNICAL INFORMATION

MATERIAL

- Insulator: High temperature engineering thermoplastic; Complies with UL94V-0, Black
- Contacts: Phosphor Bronze hard temper with Gold thickness options (6µin, 15µin, 30µin, 50µin) over 50µin min. Nickel on contact mating area. 100µin min. matte tin plating on soldering tail
- Shield: Copper Alloy, Nickel plated with Tin dipped tail or Stainless Steel with Tin dipped tail
- LED: Pure Tin plating on LED tails

MECHANICAL PERFORMANCE

- Insertion Force: 5lbs max.
- Pull Retention Force: 20lbs min.
- Durability: 750 mating and unmating cycles
- Operating Temperature Range: -55°C to +85°C
- Recommended Soldering Temperature: Wave soldering peaked at 260°C for 5 seconds max.

ELECTRICAL PERFORMANCE

- Contact Resistance: 20mΩ max.
- Insulation Resistance: 500MΩ min. at 500VDC for 2 minutes max.
- Current Rating: 1.5A
- Voltage Rating: 125VAC
- Dielectric Withstanding Voltage: 1000VAC, 60Hz, 1 minute

PACKAGING

- Tray and Tape
- Reel

APPROVALS AND CERTIFICATIONS

- RoHS
- REACH
- UL

TARGET MARKETS/APPLICATIONS



5G Wireless
Telephones
Modems
Fax Machines
Copiers/Printers



Security Systems
Set Top Boxes
Video Game Systems
PCs
Laptops



Storage
Servers
Routers
Switches
Hubs



Uninterruptible Power Supply (UPS)
ATMs
Vending Machines
POS Terminals
Industrial IoT Platforms



Analysis Equipment
Mass Spectrometers

PART NUMBERS

Product	Description	Part Numbers
RJE05 Modular Jack Series	Single port, 4P4C, without shield	RJE05-144-0X10
RJE05 Modular Jack Series	Single port, 4P4C, shielded with top& side tabs and front PCB tabs	RJE05-144-5X10
RJE05 Modular Jack Series	Single port, 6P6C, without shield	RJE05-166-0XX0
RJE05 Modular Jack Series	Single port, 8P8C, shield with top& side tabs and front PCB tabs	RJE05-188-2X10
RJE05 Modular Jack Series	Single port, 10P10C, shield without EMI tabs and with front PCB tabs	RJE05-1AA-1X10

Find part number details using the search box on www.amphenol-cs.com