



P/N	Signal NO.	Power NO.	DIM"A"	DIM"B"	DIM"C"	DIM"D"	DIM"E"
-X05020LF	05	02	14.85	13.80	8.70	4.00	12.21
-X05040LF	05	04	20.85	19.80	14.70	4.00	18.21
-X05060LF	05	06	26.85	25.80	20.70	4.00	24.21
-X05080LF	05	08	32.85	31.80	26.70	4.00	30.21
-X07020LF	07	02	16.85	15.80	10.70	6.00	14.21
-X07040LF	07	04	22.85	21.80	16.70	6.00	20.21
-X07060LF	07	06	28.85	27.80	22.70	6.00	26.21
-X07080LF	07	08	34.85	33.80	28.70	6.00	32.21
-X09020LF	09	02	18.85	17.80	12.70	8.00	16.21
-X09040LF	09	04	24.85	23.80	18.70	8.00	22.21
-X09060LF	09	06	30.85	29.80	24.70	8.00	28.21
-X09080LF	09	08	36.85	35.80	30.70	8.00	34.21
-X11020LF	11	02	20.85	19.80	14.70	10.00	18.21
-X11040LF	11	04	26.85	25.80	20.70	10.00	24.21
-X11060LF	11	06	32.85	31.80	26.70	10.00	30.21
-X11080LF	11	08	38.85	37.80	32.70	10.00	36.21
-X13020LF	13	02	22.85	21.80	16.70	12.00	20.21
-X13040LF	13	04	28.85	27.80	22.70	12.00	26.21
-X13060LF	13	06	34.85	33.80	28.70	12.00	32.21
-X13080LF	13	08	40.85	39.80	34.70	12.00	38.21
-X15020LF	15	02	24.85	23.80	18.70	14.00	22.21
-X15040LF	15	04	30.85	29.80	24.70	14.00	28.21
-X15060LF	15	06	36.85	35.80	30.70	14.00	34.21
-X15080LF	15	08	42.85	41.80	36.70	14.00	40.21
-X17020LF	17	02	26.85	25.80	20.70	16.00	24.21
-X17040LF	17	04	32.85	31.80	26.70	16.00	30.21
-X17060LF	17	06	38.85	37.80	32.70	16.00	36.21
-X17080LF	17	08	44.85	43.80	38.70	16.00	42.21
-X19020LF	19	02	28.85	27.80	22.70	18.00	26.21
-X19040LF	19	04	34.85	33.80	28.70	18.00	32.21
-X19060LF	19	06	40.85	39.80	34.70	18.00	38.21
-X19080LF	19	08	46.85	45.80	40.70	18.00	44.21

8. PRODUCT DESCRIPTION CODE :

10162695-X XX XX 0 LF

Material&Color  
0=BLACK  
1=NATURAL

RoHS COMPATIBLE  
, SEE NOTE 2  
PACKAGE

NUMBER OF SIGNAL POS.:  
TOTAL 05~19PINS (UNEVEN)

NUMBER OF POWER POS.:  
TOTAL 02~08PINS (EVEN)

NOTES:

- MATERIAL: PA66, COLOR NATURAL OR BLACK, UL94 V-0
- RoHS COMPATIBLE PRODUCT SPECIFICATIONS
  - a - LABELLING: MEETS PACKAGING SPECS AS PER GS-14-2813;
  - b - LEGAL STATEMENT: SEE GS-47-0004.
- TO USE WITH APH TERMINAL: 10162696 SERIES FOR SIGNAL, 10162697 SERIES FOR POWER
- TO BE MATED WITH AICC 10162688 & 10162689 SERIES
- PRODUCT SPEC.:GS-12-1702;
- APPLICATION SPEC.:GS-20-0703;
- THE PRODUCT IS NOT INTENDED TO BE EXPOSED TO ANY SOLDER PROCESS.

spec ref	dr	Arthur Zhao	2021/09/27	projection	mm	size	A3	scale	N/A
tolerance std	eng	Jeffrey Huang	2024/08/20			ecn no	ELX-N-52592-1	rel level	Released
ISO 406 ISO 1101	chr	-	-						
surface	linear	0.X	±0.3		Receptacle Housing ComboLock Connector	dwg no	10162695	rev	D
		0.XX	±0.2						
		0.XXX	±0.05						
ISO 1302	angular	0°	±2°	cat. no.	Product - Customer Drw	sheet 1 of 1			